

# Accessory

## CB-DVI-D

### DVI-D (M) to DVI-D (M) single link cable

#### SPECIFICATIONS

- ◆ Length: 200cm

#### ORDERING INFORMATION

- ◆ CB-DVI-D : DVI-D (M) to DVI-D (M) single link cable



## U160-CB01

### Internal Ultra160 SCSI Cable

#### SPECIFICATIONS

- ◆ Designed for Ultra160 SCSI standard
- ◆ 68-pin to 68-pin connection, max. 5 devices connection (W/O terminator)
- ◆ Shipped with one terminator
- ◆ Length: 80cm

#### ORDERING INFORMATION

- ◆ U160-CB01 : Ultra 160 SCSI cable with Terminator



## CB-USB02

### Dual Port USB Cable

#### SPECIFICATIONS

- ◆ The most suitable USB cable for ICP CPU board
- ◆ Equipped with bracket for easy installation
- ◆ 4-pin female connector to CPU board
- ◆ Length: 30cm



Pin 1, Red	Pin 2, White	Pin 3, Green	Pin 4, Black
+5V	Data-	Data+	Ground

#### ORDERING INFORMATION

- ◆ CB-USB02 : Dual port USB cable

## CB-IEEE1394

#### SPECIFICATIONS

- ◆ The most suitable USB cable for ICP CPU board
- ◆ Equipped with bracket for easy installation
- ◆ 8-pin female connector to CPU boardz
- ◆ Length: 25cm



Pin 1, White	Pin 2, Black	Pin 3, Red	Pin 4, Green
+12V	GND	TPB-	TPB+
Pin 5, Orange	Pin 6, Blue	Pin 7,	Pin 8,
TPA-	TPA+	SHIELD	SHIELD

#### ORDERING INFORMATION

- ◆ CB-IEE1394 :Dual port IEEE-1394 cable

## CVT-S6850

### Wide-SCSI 68-pin to 50-pin converter

#### ORDERING INFORMATION

- ◆ CVT-S6850: Converting from Wide SCSI 68-pin to 50-pin devices



## CVT-4044

### IDE HDD converter from 40-pin to 44-pin

#### ORDERING INFORMATION

- ◆ CVT-4044: Converting from IDE 40-pin to 44-pin devices



## CB-U160EXT


### External Ultra160 SCSI Connector

#### SPECIFICATIONS

- ◆ Designed for Ultra160 SCSI standard
- ◆ 68-pin to 68-pin connection
- ◆ Shipping with bracket panel for chassis application
- ◆ Length: 26cm

#### ORDERING INFORMATION

- ◆ CB-U160EXT : External Ultra 160 SCSI connector with bracket



## IR210L

### Infrared Data Communication Adapter

#### SPECIFICATIONS

- ◆ Meets IrDA 1.0 specification
- ◆ An integral 115cm cable with DIN connector
- ◆ IR Interface: IrDA-IR type
- ◆ Transmission speed: 9.6K~115.2Kbps
- ◆ Power Consumption: 0.3W

#### ORDERING INFORMATION

- ◆ IR210L : Infrared data communication adapter



## CB-HD32

### HDD Cable for 2.5" HDD

#### SPECIFICATIONS

- ◆ Connecting between SBC to 2.5" HDD
- ◆ 40-pin, 2.54mm pitch connector to SBC;
- ◆ 44-pin, 2.00mm pitch connector to HDD
- ◆ Standard power connector to power supply
- ◆ Length: 40cm

#### ORDERING INFORMATION

- ◆ CB-HD32 : HDD cable for 2.5" HDD



## CB-U100 Series

### For EC series 1U/2U chassis support ATA-66/100 IDE HDD 40-pin/80 wire cable

#### SPECIFICATIONS

- ◆UL-VSVC AWG30\*20P\*2 (UL20276) material Round Cable

#### ORDERING INFORMATION

- ◆ 32000-026900 45cm length cable 2 x 40-pin connector with pull-tab
- ◆ 32000-026600 45cm + 20cm length 3 x 40 pin connector with pull-tab
- ◆ 32000-026800 75cm length 2 x 40-pin connector with pull-tab
- ◆ 32000-026700 70cm + 20cm length 3 x 40-pin connector with pull-tab



32000-026900

32000-026600

32000-026700

32000-026800